

Catalog of G Series

Integrated Solar Street Light Outdoor Lighting

Features

High class Integrated die-casting Aluminum alloy case .

Lighting mode with motion senor.

120° view angle.

Over 3 nights lighting after full charge.

Easy to install, Auto on/off.

Above 30W (including)

With remote control

UVA technology

Bring high corrosion resistance


30m remote control operation

Increase/decrease the brightness



Components





Bridgelux Led Chip



Mono Solar Panel




MPPT Controller



Lithium/LifePO4 Battery



Human Body Sensor



Switch









CRH Deisgn AIO Solar Street Light

Model	GS-G10	LED	10W (Life time 100000hours)	Lighting mode
Lumen(LM)	1000LM	Colour Temperature	2700K ~6500K	25% dim light + motion sensor
Li-ion Battery	72WH 12V (life time 4-5years)	Solar Panel	18V 12W Imported High Efficiency Monocrystalline Silicon (Life time 25 years)	(Bright lighting 30secs when people move through the light) (Customzied
Mounting Height	3~4m	Cloudy/Rainy days	3 Cloudy/Rainy days	Lighitng mode is available)
Material	High Class Aluminum (Anodic oxidation process)	Working Temperature	-25°C to 65°C	Application: Courtyard/Garden/Park /Street/Roadway/pathw ay/ParkingLot/Privater oad/Sidewalk/Publicsq uare/plaza/Campus/Air field/Farm & Ranch/Perimeter Security/ Wildlife area/Remote Area/Military Base
Certificates	CE, ROHS, IP65, ISO9001	Warranty	3 Years	
Product size	530*235*150mm	Net weight	4.2kg	







CRH Deisgn AIO Solar Street Light				
Model	GS-G20	LED	20W Life time 100000hours)	Lighting mode
Lumen(LM)	2000LM	Colour Temperature	2700K ~6500K	25% dim light + motion sensor (Bright lighting 30secs when people move through the light) (Customzied Lighitng mode is available)
LifePO4 Battery	144WH 12.8V (life time 5-8 years)	Solar Panel	18V 25W Imported High Efficiency Monocrystalline Silicon (Life time 25 years)	
Mounting Height	4~5m	Cloudy/Rainy days	3 Cloudy/Rainy days	
Material	High Class Aluminum (Anodic oxidation process)	Working Temperature	-25°C to 65°C	Application: Courtyard/Garden/Park/ Street/Roadway/pathway /ParkingLot/Privateroad/ Sidewalk/Publicsquare/p laza/Campus/Airfield/Far m & Ranch/Perimeter Security/ Wildlife area/Remote Area/Military Base
Certificates	CE, ROHS, IP65, ISO9001	Warranty	3-5 Years	
Product size	840*235*150mm	Net weight	6.5kg	







CRH Deisgn AIO Solar Street Light				
Model	GS-G30	LED	30W Life time 100000hours)	Lighting mode
Lumen(LM)	3000LM	Colour Temperature	2700K ~6500K	25% dim light + motion sensor (Bright lighting 30secs when people move through the light) (Customzied Lighitng mode is available)
LifePO4 Battery	252WH 12.8V (life time 5-8 years)	Solar Panel	18V 35W Imported High Efficiency Monocrystalline Silicon (Life time 25 years)	
Mounting Height	5~6m	Cloudy/Rainy days	3 Cloudy/Rainy days	
Material	High Class Aluminum (Anodic oxidation process)	Working Temperature	-25°C to 65°C	Application: Courtyard/Garden/Park/ Street/Roadway/pathway /ParkingLot/Privateroad/ Sidewalk/Publicsquare/p laza/Campus/Airfield/Far m & Ranch/Perimeter Security/ Wildlife area/Remote Area/Military Base
Certificates	CE, ROHS, IP65, ISO9001	Warranty	3-5 Years	
Product size	1100*235*150mm	Net weight	8.5kg	







CRH Deisgn AIO Solar Street Light				
Model	GS-G50	LED	50W Life time 100000hours)	Lighting mode
Lumen(LM)	5000LM	Colour Temperature	2700K ~6500K	25% dim light + motion sensor (Bright lighting 30secs when people move through the light) (Customzied Lighitng mode is available)
LifePO4 Battery	360WH 12.8V (life time 5-8 years)	Solar Panel	18V 50W Imported High Efficiency Monocrystalline Silicon (Life time 25 years)	
Mounting Height	6~7m	Cloudy/Rainy days	3 Cloudy/Rainy days	
Material	High Class Aluminum (Anodic oxidation process)	Working Temperature	-25°C to 65°C	Application: Courtyard/Garden/Park/St reet/Roadway/pathway/P arkingLot/Privateroad/Sid ewalk/Publicsquare/plaza /Campus/Airfield/Farm & Ranch/Perimeter Security/ Wildlife area/Remote Area/Military Base
Certificates	CE, ROHS, IP65, ISO9001	Warranty	3-5 Years	
Product size	1630*435*234mm	Net weight	10.9kg/2.5kg	







CRH Deisgn AIO Solar Street Light				
Model	GS-G80	LED	80W Life time 100000hours)	Lighting mode
Lumen(LM)	8000LM	Colour Tempreture	2700K ~6500K	25% dim light + motion sensor (Bright lighting 30secs when people move through the light) (Customzied Lighitng mode is available)
LifePO4 Battery	480WH 12.8V (life time 5-8 years)	Solar Panel	18V 80W Imported High Efficiency Monocrystalline Silicon (Life time 25 years)	
Mounting Height	7~8m	Cloudy/Rainy days	3 Cloudy/Rainy days	
Material	High Class Aluminum (Anodic oxidation process)	Working Tempreture	-25°C to 65°C	Application: Courtyard/Garden/Park/ Street/Roadway/pathway /ParkingLot/Privateroad/ Sidewalk/Publicsquare/p laza/Campus/Airfield/Far m & Ranch/Perimeter Security/ Wildlife area/Remote Area/Military Base
Certificates	CE, ROHS, IP65, ISO9001	Warranty	3-5 Years	
Product size	2000*435*234mm	Net weight	13kg/2.5kg	

Applications:

Courtyard/Garden/Park/Street/Road/Pathway/ParkingLot/Privateroad/Sidewalk/plaza/Campus/Airfield/Farm & Ranch/Perimeter Security/ Wildlife area/Remote Area/Military Base














How to install and how it work?













Inteligent Lighting Mode

When people pass by, the lamp is 100% power lighting when motion sensor detect the moving. When people pass away, the lamp will remain 100% power lighting for 30sec, then will automatically turn to 30% power lighting.





Production and Packing
















Certificates



















The most professional and rigorous technical support to your success.

最专业严谨的技术支持,为您的成功保驾护航。





Project Case


Export to all over the world



USA







info@goatsun.com

WWW.GOATSUN.COM



Indonesia





info@goatsun.com

WWW.GOATSUN.COM



Costa Rica











Pakistan

